

Technical Data Sheet

CODE 16107

CA 100 MD

In-line centrifugal fans in metal



Certifications




CB TEST CERTIFICATE

Technical and performance data

Frequency (Hz)	50-60	Airflow at 1st speed (l/s)	61
Insulation class	II°	Airflow at 1st speed (m³/h)	220
IP	44	Max airflow at Max speed (l/s)	94
Max absorbed current at Max speed (A)	0,40	Max airflow at Max speed (m³/h)	340
Max absorbed current at Min speed (A)	0,30	Max pressure at Max speed (mmH2O)	39
Max absorbed Power at 60 Hz (W)	100	Max pressure at Max speed (Pa)	383
Max absorbed power at Max speed (W)	85	Max RPM	2450
Max ambient temperature for continuous operation (°C)	50	Min RPM	1730
Nominal diameter (mm)	100	Pressure at 1st speed (mmH2O)	30
Power absorbed at 1st speed (W)	60	Pressure at 1st speed (Pa)	294
Voltage (V)	220-240	Sound pressure at 3 m - min speed Lp [dB (A)] 3m - min speed	32.2
Weight (Kg)	2,97	Sound pressure at 3m at Max speed Lp [dB (A)]	43.2

Dimensions



Size A (mm)	255
Size B (mm)	239
Size C (mm)	300
Size D (mm)	97
Size E (mm)	15
Size F (mm)	15

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND
Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

Technical Data Sheet

CODE 16107

CA 100 MD


In-line centrifugal fans in metal



Description

- Pickled and phosphated steel housing with polyester powder-coated finish, resistant to the aggressive action of atmospheric agents.
- Nominal diameter 100 mm.
- 2 speed AC motor with thermal overload cutout and shaft turning in ball bearings, coupled to backward curved centrifugal impeller.
- Operation controllable by remote sensors monitoring: Temperature, Relative Humidity, Smoke and Presence.
- Zinc-coated steel brackets for wall mounting.
- IMQ SAFETY and IMQ PERFORMANCE certifications.
- Speed adjustable through Vortice speed control.

Curves



Accessories



KIT SCB (TRASF.E.C.)

Code 22481



CA-MU (STAFFE DI SOSTEGNO)

Code 22674



C 1.5 (COMANDO EL. 1.5 A)

Code 12966



C 2.5 (COMANDO EL. 2.5 A)

Code 12967



TRIO-CA

Code 12869

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com