

Technical Data Sheet

CODE 16038

CA 200 VO E

In-line centrifugal fans in self-extinguishing plastic



Certifications





IMQ Performance



TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50-60	Weight (Kg)	3,5
Insulation class	II°	Airflow at 1st speed (l/s)	107.5
IP	44	Airflow at 1st speed (m ³ /h)	387.1
Max absorbed current (A)	0,40	Max airflow at Max speed (l/s)	215.3
Max absorbed current at Min speed (A)	0.35	Max airflow at Max speed (m ³ /h)	775
Max absorbed power (W)	90	Max pressure at Max speed (mmH2O)	42.2
Max absorbed Power at 60 Hz (W)	120	Max pressure at Max speed (Pa)	413.9
Max ambient temperature for continuous operation (°C)	45	Max RPM	2611
Nominal diameter (mm)	200	Min RPM	1320
Power absorbed at 1st speed (W)	39	Pressure at 1st speed (mmH2O)	24.6
Voltage (V)	220-240	Pressure at 1st speed (Pa)	241.2
		Sound pressure at 3m at Max speed Lp [dB (A)]	50.3

DIMENSIONS



Size A (mm)	340
Size B (mm)	280
Size C (mm)	340
Size D (mm)	197
Size E (mm)	40
Size F (mm)	30
Size G (mm)	390

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com

Technical Data Sheet

CODE 16038

CA 200 V0 E

In-line centrifugal fans in self-extinguishing plastic



DESCRIPTION

- Material: self-extinguishing PP thermoplastic resin, rated V0.
- Nominal diameter 200 mm.
- 3 speed fan consisting of:
 - AC motor with thermal overload cutout and shaft turning in ball bearings,
 - backward curved impeller.
- Operation controllable by remote sensors monitoring: Temperature, Relative Humidity, Smoke and Presence.
- Zinc-coated steel brackets for wall mounting.

ACCESSORIES



**C 1.5
(COMANDO EL.
1.5 A)**

Code 12966



**KIT SCB
(TRASF.E.C.)**

Code 22481



TRIO-CA

Code 12869



**CA-MU (STAFFE
DI SOSTEGNO)**

Code 22674



**C 2.5
(COMANDO EL.
2.5 A)**

Code 12967



**CA-G 200
(GRIGLIA DI
PROTEZIONE)**

Code 22765



**SCNRB
SCAT.COM.NON
REV.INCASSO**

Code 12971



C TEMP

Code 12992



C SMOKE

Code 12993



C HCS

Code 12994



C PIR

Code 12998

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com



C TIMER

Code 12999