

Technical Data Sheet

CODE 41157

E 504 T

Low-pressure plate axial fans





Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed current at 220 V (A)	0,74	Max temperature of exhaust air (continuous operation)	70
Absorbed current at 240 V (A)	0,74	Motor ATEX marking	44
Absorbed current at 380 V (A)	0,43	Nominal diameter (mm)	500
Absorbed current at 415 V (A)	0,43	Number of poles	4
Absorbed power at 220 V (W)	235	Voltage (V)	220/380 240/415
Absorbed power at 240 V (W)	245	Weight (Kg)	8,5
Frequency (Hz)	50	Max airflow (l/s)	1333
Insulation class	I°	Max airflow (m³/h)	4800
Max absorbed current (A)	0,74	Max pressure (mmH2O)	17,7
Max absorbed power (W)	245	Max pressure (Pa)	115
Max ambient temperature for continuous operation (°C)	70	RPM	1400

DIMENSIONS



Ø (mm)	500
Size A (mm)	630
Size B (mm)	530
Size C (mm)	269
Size D (mm)	Ø
Size D3 (mm)	Ø
Size E (mm)	500
Size F (mm)	85
Size G (mm)	12
	15

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com

Technical Data Sheet

CODE 41157

E 504 T

Low-pressure plate axial fans



DESCRIPTION

- Nominal diameter 500 mm
- Wall-mounting panel manufactured from phosphated pressed steel, polyester powder coated with hammered effect finish, guaranteeing long-term resistance to atmospheric agents.
- Ventilation port fashioned in one piece with the panel and gauged to optimize air flow.
- Protective grille (in accordance with UNI ISO 13857 standard) combining the function of motor bracket, made of electrically welded steel with epoxy paint finish, colour black. Easy removal simplifies maintenance and cleaning of the fan.
- 1 speed asynchronous three-phase AC motor with shaft turning in double shielded ball bearings, insulation class F.
- Maximum air flow: 4,800 m³/h.
- Impeller with 6 wing profile blades keyed to a diecast aluminium hub and dynamically balanced (UNI ISO 1940 – Balancing class 6.3), optimized to deliver maximum performance and low noise levels, moulded from filled polypropylene for superior dimensional stability and resistance to atmospheric agents.
- Vortice speed controller.

ACCESSORIES




IRT 15

Code 12923



PGR 450/500 (PERSIANA (GRAVITA'))

Code 50550



TRA 450/500 (TELAIO CON RETE ANTINF.)

Code 51550



IRET INVERTER 2,5 M

Code 12816

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:
prevendita@vortice-italy.com

After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:
sales@vortice.ltd.uk

Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:
export@vortice-italy.com

After Sales:
after-sales@vortice-italy.com