

Wohler VIS 350 Service Camera

TECHNICAL DATA

Monitor

Dimensions housing.....7" x 4.5" x 1.3"
 TFT-Display.....7" / 16:9 format
 Video-Out.....FBAS signal
 Weight.....1 lbs

Power Supply

Power supply.....Space for 2 rechargeable batteries, each 12 V or
 via power pack
 Battery operating time.....Max. 2 rechargeable batteries, each 120 mins. = 4 h
 (battery status in display)

Pan & tilt 1.5" dia color camera head

Type.....1/3" COLOR CMOS
 Pixels.....656 x 492 (NTSC)
 Light sensitivity.....0.5 Lux
 Lens.....f = 0.09", F = 2.5
 Viewing angle.....115°
 Light source.....12 white LEDs
 Degree of protection.....Waterproof to IP 67
 Dimensions.....1 1/2" dia x 2"
 Operating temperature.....32...104 °F, RH 95 % MAX
 Storage temperature.....-4...122 °F, RH 95 % MAX

Locator transmitter

Transmission frequency.....8.9 kHz

Push rod

Length.....100 ft.
 Diameter.....0.33"

Plastic case

Dimensions.....20" x 17" x 7" (l x w x h)
 Weight.....18 lbs

Distance measurement

Wohler VIS 350 / VIS 300.....Electronic meter counter

Locator receiver

Display.....Graphic visualization of transmitted position

Output impedance

Headphones.....32 Ohm
 Power supply.....12 V MIMH battery (rechargeable)
 Operating temperature.....32...104 °F
 Storage temperature.....14 °F...104 °F
 Weight.....1.3 lbs
 Dimensions.....13" x 6" x 3" cm (l x w x h)

Memory (Wohler VIS 350)

Recording.....4 GB SD card (2.5 h recording capacity)
 Interface.....Mini USB port